

---

# Environment Variables

---

Name	Description	Required
PREDICATE_API	Base path to the Predicate API (example: <code>"/api"</code> )	Yes
TITLE	Application title displayed in the logging interface (example: <code>"Predicate"</code> )	Yes
SUBTITLE	Application subtitle displayed in the logging interface (example: <code>"Metric Store - ML Model Validation"</code> )	Yes
KEYCLOAK_URL	Keycloak URL for authorization, usually matches the one specified in the backend (example: <code>"https://&lt;keycloak-url&gt;/auth"</code> )	Yes
KEYCLOAK_REALM	Realm name in Keycloak (example: <code>"dev"</code> )	Yes
KEYCLOAK_CLIENT_ID	Client ID in Keycloak (example: <code>"kolmogorov"</code> )	Yes
KEYCLOAK_CLIENT_SECRET	Keycloak client secret, default is empty (example: <code>" "</code> )	Yes
TZ	Time zone (example: <code>"Europe/Moscow"</code> )	Yes
SENTRY_ENABLED	Flag indicating whether the Sentry service for error tracking is enabled (example: <code>"true"</code> )	Yes
SENTRY_DNS	DNS address of the Sentry project (example: <code>"https://&lt;url-sentry-project&gt;/&lt;project_number&gt;"</code> )	Yes

