
Environment Variables

Name	Description	Required	Default
PREDICATE_ROOT_PATH	Base path to the Predicate API (example: <code>"/api"</code>)	Yes	""
PREDICATE_HOSTNAME	Hostname for the Predicate service (example: <code>"https://predicate-dev.k8s.datasapiences.com"</code>)	Yes	"http"
PREDICATE_DB_URL	Database URL for Predicate (example: <code>"postgresql+psycopg2://postgres:postgres@predicate-postgresql:5432/postgres"</code>)	Yes	
PREDICATE_MANAGER_CELERY_NAME	Name for the Celery manager process (example: <code>"predicate-manager"</code>)	No	"prec"

Name	Description	Required	Defa
PREDICATE_MANAGER_CELERY_CONFIG_PATH	Path to the ConfigMap with worker settings (example: <code>"/app/celery/manager/config.json"</code>)	Yes	""
PREDICATE_MANAGER_MAX_RETRIES	Maximum number of retries for the Celery manager (example: <code>"5"</code>)	No	"5"
PREDICATE_MANAGER_RETRY_BACKOFF	Whether to use retry backoff for the Celery manager (example: <code>"True"</code>)	No	"True"
PREDICATE_MANAGER_DEFAULT_RETRY_DELAY	Default retry delay for the Celery manager in seconds (example: <code>"5"</code>)	No	"5"
PREDICATE_WORKER_CELERY_NAME	Name for the Celery worker process (example: <code>"predicate-worker"</code>)	No	"prec

Name	Description	Required	Defa
PREDICATE_WORKER_CELERY_CONFIG_PATH	Path to the ConfigMap with worker settings (example: <code>"/app/celery/worker/config.json"</code>)	Yes	""
PREDICATE_WORKER_MAX_RETRIES	Maximum number of retries for the Celery worker (example: <code>"5"</code>)	No	"5"
PREDICATE_WORKER_RETRY_BACKOFF	Whether to use retry backoff for the Celery worker (example: <code>"True"</code>)	No	"True"
PREDICATE_WORKER_DEFAULT_RETRY_DELAY	Default retry delay for the Celery worker in seconds (example: <code>"5"</code>)	No	"5"
PREDICATE_WORKER_LOG_PATH	Path to logs for the Celery worker (example: <code>"/tmp/logs"</code>)	Yes	"/var
PREDICATE_WORKER_DATASOURCE_DRIVER_PWD	Directory with jar files for data source	Yes	"/var

Name	Description	Required	Defa
PREDICATE_WORKER_METRIC_PWD	connections (example: "/app/drivers")	Yes	"/vai
PREDICATE_WORKER_TRANSFORM_PWD	Directory with metric code (example: "/tmp/share")	Yes	"/vai
PREDICATE_EXECUTOR_RESULT_DIR	Directory with transformation code (example: "/tmp/share")	Yes	"/vai
PREDICATE_EXECUTOR_S3_TMP_DIR	Directory for saving results within the project (example: "/tmp/result")	Yes	"/vai
KEYCLOAK_URL	Temporary S3 directory for the executor (example: "/tmp/s3")	Yes	
	URL for Keycloak authentication (example: "https://auth.k8s.data.sapience.ru/auth")		

Name	Description	Required	Defa
KEYCLOAK_REALM	Realm for Keycloak (example: "dev")	Yes	
KEYCLOAK_CLIENT_ID	Client ID for Keycloak (example: "kolmogorov")	Yes	
KEYCLOAK_ADMIN_USERNAME	Administrator username for Keycloak (example: "writer")	Yes	
KEYCLOAK_ADMIN_PASSWORD	Administrator password for Keycloak (example: "writer")	Yes	
PREDICATE_SENTRY_ENABLED	Whether Sentry is enabled for Predicate (example: "False")	No	"Fals
PREDICATE_SENTRY_DSN	Sentry DSN for Predicate (example: "")	No	
PREDICATE_WORKER_SENTRY_ENABLED	Whether Sentry is enabled for the Celery worker	No	"Fals

Name	Description	Required	Defa
PREDICATE_WORKER_SENTRY_DSN	(example: "False")	No	
PREDICATE_WORKER_SENTRY_DSN	Sentry DSN for the Celery worker (example: " ")	No	
PREDICATE_S3_URL	S3 URL for Predicate (example: "https://st orage.yande xcloud.net")	Yes	
PREDICATE_S3_ACCESS_KEY	S3 access key for Predicate (example: "AccessKey")	Yes	
PREDICATE_S3_SECRET_ACCESS_KEY	S3 secret access key for Predicate (example: "AccessSecr et")	Yes	
PREDICATE_S3_VERIFY	Whether to verify S3 SSL certificates (example: "False")	No	"Fals

Name	Description	Required	Defa
PREDICATE_S3_BUCKET	S3 bucket name for Predicate (example: "predicate")	Yes	
PREDICATE_S3_PREFIX	S3 folder name prefix for Predicate (example: "predicate-dev")	No	"prec
PREDICATE_LOCAL_STORAGE	Whether to use local storage for Predicate (example: "False")	No	"Fals
KLMG_UTILS_NOTIFICATION_SMTP	Whether to enable SMTP notifications for projects (example: "False")	No	"Fals
KLMG_UTILS_NOTIFICATION_SMTP_CONFIG_PATH	Path to the ConfigMap with SMTP notification settings (example: "/app/notification/smtp.json")	No	
TZ	Time zone for the application (example:	Yes	"Eurc

Name	Description	Required	Defa
	"Europe/Mos cow")		